

EventRepositoryWSDL

[Download](#)

```
<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions targetNamespace="urn:service.events.services.ncsa" xmlns:impl="urn:service.events.services.ncsa" xmlns:intf="urn:service.events.services.ncsa" xmlns:apachesoap="http://xml.apache.org/xml-soap" xmlns:wsdlsoap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"/>
<!--WSDL created by Apache Axis version: 1.2.1
Built on Jun 14, 2005 (09:15:57 EDT)-->
<wsdl:types>
  <schema xmlns="http://www.w3.org/2001/XMLSchema" targetNamespace="urn:service.events.services.ncsa" elementFormDefault="qualified">
    <element name="removeNoReply">
      <complexType>
        <sequence>
          <element name="in0" type="impl:EventQuery"/>
        </sequence>
      </complexType>
    </element>
    <complexType name="EventQuery">
      <sequence>
        <element name="after" nillable="true" type="xsd:long"/>
        <element name="baseUri" nillable="true" type="xsd:string"/>
        <element name="before" nillable="true" type="xsd:long"/>
        <element name="groupId" nillable="true" type="xsd:string"/>
        <element name="lastId" nillable="true" type="xsd:int"/>
        <element name="node" nillable="true" type="xsd:string"/>
        <element name="producer" nillable="true" type="xsd:string"/>
        <element name="script" nillable="true" type="xsd:string"/>
        <element name="task" nillable="true" type="xsd:string"/>
        <element name="topic" nillable="true" type="xsd:string"/>
        <element name="type" nillable="true" type="xsd:string"/>
        <element name="workflow" nillable="true" type="xsd:string"/>
      </sequence>
    </complexType>
    <element name="removeNoReplyResponse">
      <complexType/>
    </element>
    <element name="logEvents">
      <complexType>
        <sequence>
          <element name="in0" type="impl:EventQuery"/>
        </sequence>
      </complexType>
    </element>
    <element name="logEventsResponse">
      <complexType>
        <sequence>
          <element name="logEventsReturn" type="xsd:string"/>
        </sequence>
      </complexType>
    </element>
    <element name="count">
      <complexType>
        <sequence>
          <element name="in0" type="impl:EventQuery"/>
        </sequence>
      </complexType>
    </element>
    <element name="countResponse">
      <complexType>
        <sequence>
          <element name="countReturn" type="xsd:long"/>
        </sequence>
      </complexType>
    </element>
  </schema>
</wsdl:types>
```

```

<element name="remove">
  <complexType>
    <sequence>
      <element name="in0" type="impl:EventQuery"/>
    </sequence>
  </complexType>
</element>
<element name="removeResponse">
  <complexType>
    <sequence>
      <element name="removeReturn" type="impl:EventDescriptor" maxOccurs="unbounded"/>
    </sequence>
  </complexType>
</element>
<complexType name="EventDescriptor">
  <sequence>
    <element name="className" nillable="true" type="xsd:string"/>
    <element name="id" nillable="true" type="xsd:int"/>
    <element name="xml" nillable="true" type="xsd:string"/>
  </sequence>
</complexType>
<element name="select">
  <complexType>
    <sequence>
      <element name="in0" type="impl:EventQuery"/>
    </sequence>
  </complexType>
</element>
<element name="selectResponse">
  <complexType>
    <sequence>
      <element name="selectReturn" type="impl:EventDescriptor" maxOccurs="unbounded"/>
    </sequence>
  </complexType>
</element>
</schema>
</wsdl:types>
<wsdl:message name="countResponse">
  <wsdl:part name="parameters" element="impl:countResponse"/>
</wsdl:message>
<wsdl:message name="removeResponse">
  <wsdl:part name="parameters" element="impl:removeResponse"/>
</wsdl:message>
<wsdl:message name="logEventsResponse">
  <wsdl:part name="parameters" element="impl:logEventsResponse"/>
</wsdl:message>
<wsdl:message name="logEventsRequest">
  <wsdl:part name="parameters" element="impl:logEvents"/>
</wsdl:message>
<wsdl:message name="selectResponse">
  <wsdl:part name="parameters" element="impl:selectResponse"/>
</wsdl:message>
<wsdl:message name="countRequest">
  <wsdl:part name="parameters" element="impl:count"/>
</wsdl:message>
<wsdl:message name="selectRequest">
  <wsdl:part name="parameters" element="impl:select"/>
</wsdl:message>
<wsdl:message name="removeNoReplyResponse">
  <wsdl:part name="parameters" element="impl:removeNoReplyResponse"/>
</wsdl:message>
<wsdl:message name="removeRequest">
  <wsdl:part name="parameters" element="impl:remove"/>
</wsdl:message>
<wsdl:message name="removeNoReplyRequest">
  <wsdl:part name="parameters" element="impl:removeNoReply"/>
</wsdl:message>
<wsdl:portType name="EventRepository">
  <wsdl:operation name="removeNoReply">
    <wsdl:input name="removeNoReplyRequest" message="impl:removeNoReplyRequest"/>
    <wsdl:output name="removeNoReplyResponse" message="impl:removeNoReplyResponse"/>
  </wsdl:operation>
</wsdl:portType>

```

```

</wsdl:operation>
<wsdl:operation name="logEvents">
    <wsdl:input name="logEventsRequest" message="impl:logEventsRequest"/>
    <wsdl:output name="logEventsResponse" message="impl:logEventsResponse"/>
</wsdl:operation>
<wsdl:operation name="count">
    <wsdl:input name="countRequest" message="impl:countRequest"/>
    <wsdl:output name="countResponse" message="impl:countResponse"/>
</wsdl:operation>
<wsdl:operation name="remove">
    <wsdl:input name="removeRequest" message="impl:removeRequest"/>
    <wsdl:output name="removeResponse" message="impl:removeResponse"/>
</wsdl:operation>
<wsdl:operation name="select">
    <wsdl:input name="selectRequest" message="impl:selectRequest"/>
    <wsdl:output name="selectResponse" message="impl:selectResponse"/>
</wsdl:operation>
</wsdl:portType>
<wsdl:binding name="EventRepositorySoapBinding" type="impl:EventRepository">
    <wsdlsoap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="removeNoReply">
        <wsdlsoap:operation soapAction="" />
        <wsdl:input name="removeNoReplyRequest">
            <wsdlsoap:body use="literal"/>
        </wsdl:input>
        <wsdl:output name="removeNoReplyResponse">
            <wsdlsoap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="logEvents">
        <wsdlsoap:operation soapAction="" />
        <wsdl:input name="logEventsRequest">
            <wsdlsoap:body use="literal"/>
        </wsdl:input>
        <wsdl:output name="logEventsResponse">
            <wsdlsoap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="count">
        <wsdlsoap:operation soapAction="" />
        <wsdl:input name="countRequest">
            <wsdlsoap:body use="literal"/>
        </wsdl:input>
        <wsdl:output name="countResponse">
            <wsdlsoap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="remove">
        <wsdlsoap:operation soapAction="" />
        <wsdl:input name="removeRequest">
            <wsdlsoap:body use="literal"/>
        </wsdl:input>
        <wsdl:output name="removeResponse">
            <wsdlsoap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="select">
        <wsdlsoap:operation soapAction="" />
        <wsdl:input name="selectRequest">
            <wsdlsoap:body use="literal"/>
        </wsdl:input>
        <wsdl:output name="selectResponse">
            <wsdlsoap:body use="literal"/>
        </wsdl:output>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="EventRepositoryService">
    <wsdl:port name="EventRepository" binding="impl:EventRepositorySoapBinding">
        <wsdlsoap:address location="http://localhost:8080/events/services/EventRepository"/>
    </wsdl:port>

```

```
</wsdl:service>
</wsdl:definitions>
```